

Integrating Electronic Components into Deformable Objects Based on User Interaction Data

Paul Worgan, Kevin Reuss, Stefanie Mueller

MIT CSAIL, Cambridge, MA, USA

{pworgan, kreuss, stefanie.mueller}@mit.edu

ABSTRACT

A key challenge when designing deformable user interfaces is the integration of *rigid* electronic components with the soft deformable device. In this paper, we propose to place electronic components based on how the user is interacting with the device, i.e., in which way the device is being deformed when the user performs gestures.

To identify optimum locations for placing electronic components, we developed a design tool that takes as input a 3D model of the deformable device and a set of captured user gestures. It then visualizes the stress distribution resulting from the gestures applied to the deformable device and suggests where not to place components because the location is highly deformed when users interact (e.g., a rigid battery that would constraint interaction); or alternatively where to place components to sense deformation more accurately (e.g., a bend sensor to detect a specific gesture) and efficiently (e.g., an energy harvesting component).

We evaluated our approach by collecting interaction data from 12 users across three deformable devices (a watch, a camera, and a mouse) and applied the resulting stress distributions to the placement of selected electronic components.

Author Keywords

Organic User Interfaces; Prototyping Tools; Gestures.

ACM Classification Keywords

H5.2. [Information interfaces and presentation]: User Interfaces.

INTRODUCTION

Since the early 2000s, HCI researchers envision a future in which devices will no longer be rigid but deformable (*Organic User Interfaces* [6]). Moving away from rigid objects and being able to squeeze, stretch, and twist devices offers many advantages, including an increased input space (*Gummi* [19]), output space (*Surflex* [3]), and better ergonomics [6].

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from Permissions@acm.org.

TEI '19, March 17–20, 2019, Tempe, AZ, USA
© 2019 Association for Computing Machinery.
ACM ISBN 978-1-4503-6196-5/19/03...\$15.00
<https://doi.org/10.1145/3294109.3295629>




Figure 1. (a) Our design tool collects gesture data to help with the placement of electric components when designing deformable devices. Designers only have to (b) create a 3D model of the device & silicone cast it, (c) record interaction data, (d) feed the data back to our stress analysis tool, which then (e) suggests a placement based on areas of least or most stress (i.e., deformation).

One key challenge when designing deformable user interfaces is the integration of electronic components with the deformable device. While research points towards the development of flexible electronics, such as deformable displays (*Stretchis* [23]) and circuitry (*SiliconeDevices* [14]), many electronic components remain rigid and when placed in the wrong location interfere with the user interaction. Even for soft components, such as bend sensors and piezo-electric foils used for energy harvesting, the right placement is important since the interaction can be sensed more accurately and the energy output per gesture can be increased.

In this paper, we present a design tool that supports designers in the process of placing electronic components inside a deformable device. The key idea is to incorporate

knowledge about how the user is interacting with the device to place and orient electronic components according to a device and its corresponding gesture set.

RELATED WORK

Our research is related to organic user interfaces, work that integrates electronics with deformable devices, and grasp sensing.

Organic & Deformable User Interfaces

Over the last decade, organic user interface research has made significant progress: Many different materials and structures have been employed [17] and the space of design choices, such as material stiffness [9, 10], device size [12], and types of gestures [8, 21] and their influence on user performance and experience has been studied. However, while the field has seen large progress, there are still many challenges remaining as outlined by Alexander et al. [1]. One of these challenges is the need for toolkits to effectively prototype organic interface hardware, including the integration of functional electronic components. Only recently, researchers have started to develop such tools. For instance, *DefSense* [2] helps users design customized deformable input devices by embedding piezo-resistive wires to represent the current deformation state.

Integrating Electronics with Deformable User Interfaces

One way to seamlessly integrate electronics into deformable devices is to use only bendable and stretchable components. Screen-printing, for instance, allows for layered-fabrication of bendable and stretchable displays (*Print-Screen* [16], *Stretchis* [23]) and matching flexible circuitry can be created using either conductive inkjet printing [15], screen-printing (*Skintillates* [13]) or by filling liquid metal into channels (*SiliconeDevices* [14]). However, many electronic components remain rigid and when placed in the wrong location interfere with the user interaction.

Grasp Sensing for Interactive Systems

Grasp sensing has been studied extensively over the last decade. For a complete review we refer to Wimmer [24] who describes different aspects of grasp sensing and a variety of sensing technologies that can be employed. We built onto work by Ehrenmann et al. [5] who were among the first to use a pressure sensing data glove and a camera-system to track hand posture, position and applied forces while users are manipulating objects. Since then, pressure sensing and motion capture approaches have been used to build more detailed models of how humans interact with objects (Saidon et al. [18]) including the creation of large gesture databases with a variety of manipulation tasks involving objects ranging from kitchen utensils, to tools, mugs, jars, and toys (Verdier et al. [22]). For our work, we build on prior research in grasp sensing but use it as a means to place electronic components inside a deformable device according to user gestures.

DESIGN TOOL FOR DEFORMABLE DEVICES

Our design tool allows designers to record and process interaction data while creating a deformable device.

#1 3D Modeling of the Deformable Device

Designers start by creating the form factor of the deformable device in a 3D modeling program. Figure 1b shows the 3D model of a deformable mouse the designer created.

#2 Collecting Interaction Data

Once the 3D model is finished, designers can create a physical prototype from it (e.g., from silicone) and start recording interaction data from gestures. To accurately determine how a user deforms the device, we collect both the position of each finger on the device as well as the amount of pressure each finger applies to the device. To determine the position, we use an optical motion capture system (*OptiTrack Flex13*). As can be seen in Figure 1a, we place six cameras on a desk to track the user's interaction with the deformable device on the table. To detect the applied force during interaction, we built a custom glove with pressure sensors on the finger tips.




Figure 2. Recording Interface.

Designers can either record interactions themselves or collect data from other users. For this, we provide a custom recording interface implemented in *Unity3D* (Figure 2). The designer can add new users, specify the deformable device being used, define a gesture, and record multiple takes of a gesture. The view also shows live data from the motion capture system and displays the deformable device as a 3D model for reference. The output from a recording session is a file that the designer can load into the 3D editor for subsequent stress and placement analysis.

#3 Computing the Stress Distribution Map

In the 3D editor, the designer can now execute a custom plugin we wrote to import the interaction data (Figure 3).




Figure 3. (a) Finger imprints and applied force, (b) resulting stress distribution.

Loading the interaction data applies the finger imprints and corresponding forces from the grasp to the 3D model auto-

matically (Figure 3a) and then executes a finite element analysis to determine the stress distribution (Figure 3b).

#4 Placing Electronic Components

Based on the generated stress distribution map our system recommends a location for placing the electronic components by providing the 3D location of the most or least stress (Figure 1e), which allows the designer to make an informed decision about how to best integrate the part.

TESTING OUR SYSTEM WITH A GROUP OF USERS

We tested our workflow by recording data from 12 users recruited from our institution (1 female, age 22-44, mean: 26.91). We asked them to perform gestures with three deformable devices: a mouse, a camera, and a smart watch. The study was conducted as within-subjects and participants were randomly assigned an order. We used the same setup as described in ‘Collecting Interaction Data’, i.e. the motion capture system on a table and users were wearing the pressure sensing glove (Figure 4).

Our study contained the following tasks: (1) *Camera*: ‘Squeeze the camera lens to zoom in the image. Zoom until the tree in the image is displayed full screen.’ (2) *Smart-Watch*: ‘Squeeze the smart watch to adjust the volume of the music. Adjust the volume to 80%.’ (3) *Mouse*: ‘Squeeze the mouse to scroll the webpage. Scroll the webpage to the third headline.’

We gave users 5 minutes to familiarize themselves with the devices and the pressure sensing glove, i.e. they were allowed to perform test grasps on the deformable objects and to lift and tilt them to get a better feeling for the devices.

For each device and gesture, we briefly demonstrated how to perform it. Afterwards, users performed 20 trials per gesture. We started the recording using the ‘start’ button and stopped recording by pressing the ‘stop’ button of our recording interface (Figure 2). The data collection for each user took 20 minutes or less. The recorded data included the motion data for each finger as well as the corresponding pressure values for each finger.



Figure 4. Data collection.

Figure 5 shows example stress distributions from the collected user data for all devices and the suggested placement based on the aggregated data of all users: (a) For the deformable mouse, we asked the system to mark the area of least stress to best integrate a rigid button cell for energy supply without interfering with the user interaction. (b) For

the smart watch, we asked the system to mark the area of largest stress to place a piezo-electric foil that harvests more energy when strongly deformed. (c) For the camera, we asked the system to mark the area of least stress facing outwards to optimally place a connector for data transfer of the camera images to a computer.




Figure 5. Stress distribution and recommended placement for (a) a button cell, (b) a piezo-electric foil, (c) a data-transfer connector.

USE CASES

We next describe two example use cases that place electric components based on the stress distribution results. While our approach applies to many different domains, such as placing sensors for more accurate user interaction tracking or laying out circuitry to avoid breakage, we focus on energy supply components as brief examples.

Example #1: Energy-Harvesting (Largest Stress)

In energy harvesting, the more a piezo-electric foil is deformed, the more energy can be harvested. To demonstrate that more energy can be harvested when the piezoelectric foil is placed according to specific gestures, we ran a simple experiment. We placed two piezoelectric foils inside the deformable mouse (one left-to-right, one front-to-back). We then performed two gestures as shown in Figure 6: (1) a front-to-back squeeze (as in *Adaptive Mouse* [20]), and (2) a side-to-side squeeze (as in *Inflatable Mouse* [11]). We collected the mean energy over 10 repetitions.



Figure 6. (a) Side-to-side, (b) front-to-back.

Our results show that when the piezoelectric foil is mounted orthogonal to the direction of the performed gesture, i.e., in the location of largest stress, it generates a larger amount of energy. For instance, the opposing *side piezo* + *front-to-back* gesture generated 7 times more energy compared to

the aligned *front-to-back piezo* + *front-to-back* gesture (1.0538 μJ vs. 0.1343 μJ). Conversely, the opposing *front-to-back piezo* + *side-to-side* gesture generated over 3 times the amount of energy as the aligned *side-to-side piezo* + *side-to-side* gesture (0.6624 μJ vs. 0.1925 μJ). Thus, placing the piezo-electric foil according to the user interaction helped to increase energy supply.

Example #2: Plug-and-Socket Connector (Least Stress)

Connectors are sensitive to deformation since the plug and socket may delaminate and lose the electric connection. To demonstrate that placing connectors in the areas of least stress reduces delamination, we ran another experiment. First, we created a soft plug-and-socket connector (silicone, flexible copper tape contacts) to reduce the chance of breakage in general (Figure 7). Next, we measured how much the connector delaminates (changes in contact resistance) by subjecting the connector to different bend radii.




Figure 7. Deformable connector integrated into a deformable phone that folds along the long side.

We found that for bend angles from -70° (bend away from connector) to 0° (no bending) to $+20^\circ$ (bend towards connector) the contact resistance was approximately $60\text{m}\Omega$. For larger angles, however, the quality of the connection dropped quickly ($+25^\circ = 210\text{ m}\Omega$, $+30^\circ = 330\text{ m}\Omega$). Thus, placing the connector according to the gesture was important to maintain a good electric connection.

IMPLEMENTATION

Our recording interface is implemented in *Unity3D* using C#. To apply the interaction data to the 3D model of the device we implemented a *SolidWorks* plugin in Visual Basic.

#1 Pressure Sensor Input

To build the pressure glove, we bought a workshop glove and attached force resistive pressure sensors (*Interlink Electronics FSR 400*) to the finger tips. We connected the force sensors to an Arduino that we enclosed in a 3D printed box and attached to the upper arm of the user. The Arduino is connected to a computer that runs a python script to collect the pressure values. Each pressure sensor returns an analog value which we map to a pressure value according to the specification (see Figure 3 in [7]). We use the pressure values in two ways: (1) during *data collection*, the data is forwarded to the application to provide users with visual feedback while performing the gesture (e.g., zooming the image in the deformable camera example). (2) When *calculating*

the stress distribution, we use the pressure values to determine the amount of force each finger applied to the device.

#2 OptiTrack Input

To enable streaming with *OptiTrack*, we activated the *Streaming Engine* in the software *Motive:Tracker*. To receive the streamed data in *Unity3D*, we attached the *OptitrackStreamingClient.cs* script to one UI element. When we receive streamed data, we convert the marker coordinates from the *OptiTrack* coordinate system to the *Unity3D* coordinate system using a scaling factor. We then assign the values from each of the pressure sensors to the corresponding finger. To identify which marker represents which finger, we perform a calibration gesture (flat hand).

#3 Generating the Specification File

Our system automatically stores all finger locations and pressures values in a file, containing *start location*, *end location*, and *pressure value* for each finger.

#4 Calculating the Stress Distribution Map

Our *SolidWorks* plugin automatically reads the file and uses the start and end coordinates of each finger to generate a direction vector that approximates the finger movement. It then generates a representation of the finger imprint by (1) creating a plane perpendicular to the direction vector, (2) placing a circle on the plane, and (3) projecting the circle along the direction vector onto the model. This results in a finger imprint on the surface of the 3D model. We then apply the corresponding pressure value to each finger imprint and run a finite element analysis. The result is a stress distribution map across the model for an individual user and an individual gesture.

To average the data over multiple gestures or users, we automatically export all stress values into a .csv file using a *Workflow Sensitive Sensor* in *SolidWorks*. We then run a custom script that averages the data and associates each stress value with a 3D coordinate resulting in a 3D array, i.e. a representation of voxels with associated stress values.

#5 Suggesting Locations for Energy Components

Our plugin then finds the combination of voxels with either least or most stress. It also checks for the size and orientation of the electronic component to fit them into the voxel grid. For this, our system contains a library of components including their length, width and height. If multiple regions are subject to the same amount of stress, we ask the designer for input.

#6 Material Properties for the Virtual Material

To represent the material properties of the silicone used for our devices, we created a custom virtual material in *SolidWorks* (i.e., we consulted the material specification sheet of the silicone we used, *Ecoflex 00-30* [4], and then transferred core characteristics, such as the shore hardness and the tensile strength to the properties of the virtual material). We assign the material automatically to the 3D model before computing the stress distribution.

DISCUSSION

While our workflow provides a first starting point to explore prototyping tools to integrate electronic components with deformable devices, we will use this section to highlight a few alternatives and directions for future work.

Motion Capture vs. Hand Simulation: While we collect gesture data from users interacting with the physical prototype of the device, interaction data can be generated through many different means. For instance, a rigged digital hand model can be used to generate different interaction patterns. We decided to use motion capture since it captures the diversity of interaction patterns among different users.

Leveraging Interaction Data for other Design Choices: While we use interaction data to place electronic components, interaction data from deformable devices can be used in many additional realms. For instance, one could harvest interaction data to generate soft compliant mechanisms that activate when specific gestures are being performed.

Aggregated vs. Individual Fit: Since the grasp pattern of each user is different, aggregated data can only provide an approximate fit. However, with advances in personal fabrication, we envision a future in which users will obtain personalized devices that are optimized specifically for them.

CONCLUSION

In this paper, we demonstrated how to leverage gesture data representing how a user is interacting with a deformable device to optimize the placement of electronic components during the design process. We demonstrated how our design tool collects interaction data from users, processes the data to generate a stress distribution map, and finally recommends a position for placing the electronic components based on locations of least or largest stress. For future work, we plan to extend our algorithm to also include the layout of wires inside the device. In addition, we will extend our work towards additional use cases in sensing and actuation.

REFERENCES

1. Jason Alexander, Anne Roudaut, Jürgen Steimle, Kasper Hornbæk, Miguel Bruns Alonso, Sean Follmer, and Timothy Merritt. Grand Challenges in Shape-Changing Interface Research. In *Proceedings of the 2018 CHI Conference on Human Factors in Computing Systems* (CHI '18), Paper 299.
2. Moritz Bächer, Benjamin Hepp, Fabrizio Pece, Paul G. Kry, Bernd Bickel, Bernhard Thomaszewski, and Otmar Hilliges. DefSense: Computational Design of Customized Deformable Input Devices. In *Proceedings of the 2016 CHI Conference on Human Factors in Computing Systems* (CHI '16), 3806-3816.
3. Marcelo Coelho, Hiroshi Ishii, and Pattie Maes. Surflex: A Programmable Surface for the Design of Tangible Interfaces. In *Extended Abstracts on Human Factors in Computing Systems* (CHI '08), 3429-3434.
4. Ecoflex 00-30 Material Specification Sheet: https://www.smooth-on.com/tb/files/ECOFLEX_SERIES_TB.pdf
5. M. Ehrenmann, R. Zollner, S. Knoop, R. Dillmann. Sensor Fusion Approaches for Observation of User Actions in Programming by Demonstration. In *IEEE International Conference on Multisensor Fusion and Integration for Intelligent Systems* (MFI'01), 227-232.
6. David Holman and Roel Vertegaal. Organic User Interfaces: Designing Computers in Any Way, Shape, or Form. In *ACM Communications* 51, 6, 48-55, 2008.
7. Interlink Electronics FSR 400 Data Sheet <https://dlnmh9ip6v2uc.cloudfront.net/datasheets/Sensors/ForceFlex/2010-10-26-DataSheet-FSR400-Layout2.pdf>
8. Audrey Girouard, Jessica Lo, Md Riyadh, Farshad Daliri, Alexander Keith Eady, and Jerome Pasquero. One-Handed Bend Interactions with Deformable Smartphones. In *Proceedings of the 33rd Annual ACM Conference on Human Factors in Computing Systems* (CHI '15), 1509-1518.
9. Johan Kildal. Interacting with Deformable User Interfaces: Effect of Material Stiffness and Type of Deformation Gesture. In *Proceedings of the 7th International Conference on Haptic and Audio Interaction Design* (HAID'12), 71-80.
10. Johan Kildal and Graham Wilson. Feeling it: The Roles of Stiffness, Deformation Range and Feedback in the Control of Deformable UI. In *Proceedings of the 14th ACM International Conference on Multimodal Interaction* (ICMI '12), 393-400.
11. Seoktae Kim, Hyunjung Kim, Boram Lee, Tek-Jin Nam and Woohun Lee. Inflatable Mouse: Volume-Adjustable Mouse with Air-Pressure-Sensitive Input and Haptic Feedback. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems* (CHI '08), 211-224.
12. Sang-su Lee, Youn-kyung Lim, and Kun-Pyo Lee. Exploring the Effects of Size on Deformable User Interfaces. In *Proceedings of the 14th International Conference on Human-Computer Interaction with Mobile Devices and Services Companion* (MobileHCI '12), 89-94.
13. Joanne Lo, Doris Jung Lin Lee, Nathan Wong, David Bui, and Eric Paulos. Skintillates: Designing and Creating Epidermal Interactions. In *Proceedings of the 2016 ACM Conference on Designing Interactive Systems* (DIS '16), 853-864.
14. Steven Nagels, Raf Ramakers, Kris Luyten, and Wim Deferme. Silicone Devices: A Scalable DIY Approach for Fabricating Self-Contained Multi-Layered Soft Circuits using Microfluidics. In *Proceedings of the 2018 CHI Conference on Human Factors in Computing Systems* (CHI '18), Paper 188.

15. Simon Olberding, Nan-Wei Gong, John Tiab, Joseph A. Paradiso, and Jürgen Steimle. A Cuttable Multi-Touch Sensor. In *Proceedings of the 26th Annual ACM Symposium on User Interface Software and Technology* (UIST '13), 245-254.
16. Simon Olberding, Michael Wessely, and Jürgen Steimle. PrintScreen: Fabricating Highly Customizable Thin-Film Touch-Displays. In *Proceedings of the 27th Annual ACM Symposium on User Interface Software and Technology* (UIST '14), 281-290.
17. Isabel P. S. Qamar, Rainer Groh, David Holman, and Anne Roudaut. HCI meets Material Science: A Literature Review of Morphing Materials for the Design of Shape-Changing Interfaces. In *Proceedings of the 2018 CHI Conference on Human Factors in Computing Systems* (CHI '18), Paper 374.
18. N. F. Elya Saidon, Chikamune Wada, Siti A. Ahmad, Ribhan Zafira Abdul Rahman, Kiyotaka Eguchi, Yoshiyuki Tomiyama and Farida Izni Abd Rahman. Real-time Human Motion Analysis and Grasping Force using the OptiTrack System and Flexi-force Sensor. In *Pertanika Journal of Science and Technology*, 25, 69-76, 2017.
19. Carsten Schwesig, Ivan Poupyrev and Eijiro Mori. Gummi: User Interface for Deformable Computers. In *Extended Abstracts on Human Factors in Computing Systems* (CHI '03), 954-955.
20. Sheng Kai Tang and Wen Yen Tang. Adaptive Mouse: A Deformable Computer Mouse Achieving Form-Function Synchronization. In *Extended Abstracts on Human Factors in Computing Systems* (CHI '10), 2785- 2792.
21. Giovanni Maria Troiano, Esben Warming Pedersen, and Kasper Hornbæk. User-Defined Gestures for Elastic, Deformable Displays. In *Proceedings of the 2014 International Working Conference on Advanced Visual Interfaces* (AVI '14), 1-8.
22. Benjamin Verdier, Sheldon Andrews, and Paul G. Kry. Human Grasping Interaction Capture and Analysis. In *Proceedings of the ACM SIGGRAPH / Eurographics Symposium on Computer Animation* (SCA '17), Article 23.
23. Michael Wessely, Theophanis Tsandilas, and Wendy E. Mackay. Stretchis: Fabricating Highly Stretchable User Interfaces. In *Proceedings of the 29th Annual Symposium on User Interface Software and Technology* (UIST '16), 697-704.
24. Raphael Wimmer. Grasp Sensing for Human-Computer Interaction. In *Proceedings of the Fifth International Conference on Tangible, Embedded, and Embodied Interaction* (TEI '11), 221-228.